material specifications

Revision 10 | November 12, 2026

bauxite LWS-515

- Material: Type II Vinyl wallcovering
- Finish: Mylar
- Backing: Non-woven
- Weight: 20 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 10
- Smoke Developed Index: 20

beach LWS-518

- Material: Type II Vinyl wallcovering
- Backing: Non-woven
- Weight: 20 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 0
- Smoke Developed Index: 0

blanc sisal LWS-521

- Material: Natural grasscloth
- Backing: Paper
- Width: 36 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 10
- Smoke Developed Index: 15

gold iridescent LWS-516

- Material: PVC-free polyester canvas
- Finish: Subtle Gold Sheen
- Backing: Non-woven
- Nominal weight: 16 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 20
- Smoke Developed Index: 20

linen LWS-519

- Material: Type II Vinyl wallcovering
- Backing: Non-woven
- Weight: 20 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 0
- Smoke Developed Index: 0

pearl LWS-522

- Material: Type II Vinyl wallcovering
- Backing: Non-woven
- Weight: 20 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 10
- Smoke Developed Index: 25

resilience LWS-525

- Material: PVC- and olefin-free nonwoven
- Composition: Cellulose and polyester
- Binder/coating: Latex and printable coating
- Weight: 14 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 15
- Smoke Developed Index: 5

shine LWS-517

- Material: Type II Vinyl wallcovering
- Backing: Poly-cotton woven
- Weight: 20 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 20
- Smoke Developed Index: 95

silk LWS-520

- Material: Type II printable vinyl wallcovering
- Backing: Woven
- Weight: 20 oz per linear yard
- Width: 54 in
- Class A fire rating
- ASTM E84
- Flame Spread Index: 10
- Smoke Developed Index: 5

look.
WALLS & INTERIORS

ASTM E84 flame and smoke values are indices. Supporting test reports govern certified results.